

Pipe Hangers

Pipe hangers are used to support a sprinkler piping system from the building structure. Two or more listed components may be required to form a complete hanger assembly. The specific components required depend upon the type of building construction and the pipe size.

C-Type Clamps

A type of clamp that is used to provide a load carrying connection to the flange of a building structural element, usually by use of a jaw and setscrew combination. It also provides for the attachment of a threaded rod.

Lindapter International, C- Type Clamps

Product Specification

Model No	Description	Hanger Rod Size, in (mm)	Nominal Pipe Size	
			in	(mm)
M10 FLS	Swivel Beam Clamp	(10)	3/4 through 4	(20 through 100)
M10 Swiftgrip	Swiftgrip Beam Clamp	3/8	3/4 through 4	(20 through 100)
M10 Swiftgrip Swivel Unit	Swiftgrip Beam Clamp with Swivel	(10)	3/4 through 4	(20 through 100)
3/8 FL S	Swivel Beam Clamp	3/8	3/4 through 4	(20 through 100)
FL 2 (Malleable Iron)	Type FL Flange Clamp	(10)	3/4 through 4	(20 through 100)
FL2 with swivel (Malleable Iron)	Type FL Flange Clamp	(10)	3/4 through 4	(20 through 100)
FL 2 (Stainless Steel)	Type FL Flange Clamp	(10)	3/4 through 4	(20 through 100)
FL 3	Type FL Flange Clamp	(12)	5 through 8	(125 through 200)
10122	Type F3 Flange Clamp	(10 through 20)	3/4 through 6	(20 through 150)
10115	Type F3 Flange Clamp	(10 through 20)	3/4 through 6	(20 through 150)

Company Name:	Lindapter International
Company Address:	Lindsay House Brackenbeck Rd, Bradford, West Yorkshire BD7 2NF, United Kingdom
Company Website:	http://lindapter.com
New/Updated Product Listing:	No
Listing Country:	United Kingdom
Certification Type:	FM Approved
Class of Work:	1951-Pipe hangers For AS Sys